


Five horizontally stacked units to make FHD



I-V LED Poster

pitch	1.5	1.8	2.0	2.5
pixel tech	SMD	SMD	SMD	SMD

ideal for

Mobile signage

summary

The Vanguard **I-V LED Poster** is a powerful all-in-one solution for digital signage. The LED Poster can run locally stored content, streaming, or locally connected source. Posters utilize a convenient Android operating system, enabling easy content maintenance.

Vanguard's **I-V LED Poster's** can be suspended or sit on the floor with either wheels or a leg to lean on. Stitch together multiple posters to create a larger display!



Video:
HDMI-IN
HDMI-OUT
USB3.0

Audio:
Ext audio interface

Control:
RJ45
WIFI
Local AP network
4G network

Sensor:
Brightness
Temperature
Humidity

optional





series name

I-V LED Poster (LP)

maximum brightness

600 nits (2.5mm 500 nits)

environmental rating

Indoor, mobile installation

viewing angle

HORIZONTAL | 160°

VERTICAL | 160°

LED half-life*

100,000 hours

contrast

8,000:1

refresh rate

3,840 Hz

frame rate

50, 60 Hz

color temperature

6,500 K

temperatures

-20°C - +50°C

operating humidity

10% - 80%, non-condensing

operating voltage

100-240V AC, 50/60 Hz

ip rating

IP30 (IP60 rear)

service access

Front (*display components*), Rear (*control box*)

warranty

5-year default (up to 7-year available)

certifications

CE ROHS ETL UL

